Z5 Series Steam Sensing Control

The Z5 Steam Switch has been designed to meet the critical technical requirements demanded by new generation kettles and jugs.

The Z5, which is manufactured in materials especially chosen for their high tracking index, also incorporates a unique patented double contact system. These features, plus small size, ensures the Z5 is suitable for all kettle and jug application positions i.e. top and bottom mounting plus 'under floor'.

A single screw fixing option accommodates both vertical and horizontal mounting and the standard 4.8 by 0.8 mm male terminals would allow the Z5 to be connected directly with the Otter X4, if required.

TECHNICAL DATA

Approvals Rating

EN	15A 240V ~
CSA	15A 240V ~
UL	15A 120/240V ~
CQC	15A 240V ~
Maximum Ambient Temperature	125°C
Flammability	Flame Retardant

FEATURES

- Small size
- Designed for all Installation options;
  - Vertical
  - Horizontal
  - Inclined
  - Underfloor
- Remote or 'plug in'
- 15 Amp Rating
- 3 kW Capability
- 3mm Contact Gap
- Flame Retardant Material
- High Tracking Index
- Actuator Fixing Options
- Designed to meet International Approval requirements

APPLICATIONS

- Jugs
- Kettles
- Water Heaters
- Vending Machines
- Hot Pots

ASSOCIATED PRODUCTS

The Z5 is an integral component of the Gemini Modular System and can be incorporated alongside any Otter element protector or cordless system. The Z5 could also close-couple with the X4 360° dry boil protector for 'underfloor' applications and also the A1 series (A11 360° dry boil control).

Otter
...always in control