



One Page Setup

- MAIN MENU**
- OnePage Setup
- ADVANCED SETUP**
- DHCP Settings
- Access Control
- Open Ports
- DMZ Host
- Special Application
- Device Admin.
- Status Monitor
- Dynamic Routing
- Static Routing
- Log
- DDNS
- Wireless
- Backup & Restore
- Upgrade Firmware
- Diagnostic-Ping/Trac

Log Out

Host Name: (Required by some ISPs)

Domain Name: (Required by some ISPs)

Private IP Address (MAC Address: 00-01-36-06-1E-2A)

Device IP Address: 192 . 168 . 1 . 1

Subnet Mask: 255.255.255.0

Wireless (MAC Address: 00-01-36-06-1E-2A)

Enable **Disable**

SSID :
(Wireless network name) (must be the same for all wireless clients)

Channel: 4 (Domain: Most of Europe/Australia)

WEP Encryption: **Enable** **Disable**

WAN Connection Type Static IP (MAC Address: 00-01-36-06-1E-2A)

Select the Internet connection type you wish to use

Specify WAN IP Address: 192 . 168 . 2 . 10

Subnet Mask: 255 . 255 . 255 . 0

Default Gateway Address: 192 . 168 . 2 . 1

DNS (Required) 1: 195 . 121 . 1 . 34

DNS 2: 195 . 121 . 1 . 66

DNS 3: 0 . 0 . 0 . 0