



HDMI Splitter / Switcher 2:4

2 Sources + 4 Displays = Greater Integration Options

Gefen's 2x4 HDMI Switcher is equipped with two HDMI inputs and four HDMI outputs. Two inputs accommodate the simultaneous connection of up to two high definition video sources, such as satellite systems and HD DVD players. four outputs send the high definition audio/video signals to up to four high definition displays. A digital audio output port is available if you need to direct the audio to an audio receiver. Switching is done via the IR remote that is provided with the unit.

This HDMI product supports BOTH Audio and Video signals.

Fully HDCP Compliant

HDCP (high bandwidth digital content protection) is a standard encoded into the video signal to prevent it from being pirated. If a source device is HDCP coded and is connected to a display or projector without the proper decoding mechanism, the picture is relegated to "snow" or in some cases, very low (480P) resolutions of the images. In order to see high resolution digital video with HDCP compliance, both the source, the display and anything in between must be equipped with HDMI connections that can enable HDCP decoding, such as the 2x4 HDMI Switcher.

How it Works

You simply connect all your sources to the Switcher's inputs. Then connect up to four displays on the output ports. Once the sources, the Switcher and the display(s) are powered and connected, you simply select which source you want to view using the IR remote.



Package Includes:

- The 2x4 HDMI Switcher
- RMT-2IR Remote Control
- Two 6-foot HDMI cables
- 5VDC Power Supply
- User's Manual

Features:

- Switch easily between any two HDMI sources
- Outputs are mirrored to four HDMI displays
- Maintains 480p, 720p, 1080i, and 1080p resolutions
- Maintains high resolution video - beautiful HDTV resolutions up to 1080p are easily achieved.
- Discrete IR remote (included)
- Fully HDMI 1.2 compliant
- HDCP compliant
- Easy to install and simple to operate

Specifications:

- Video Amplifier Bandwidth: 1.65 Gbps
- Input Video Signal: 1.2 volts p-p
- Input DDC Signal: 5 volts p-p (TTL)
- Single Link Range: 1080p/1920 x 1200
- HDMI Connector: Type A 19pin female
- Power Supply: 5V DC
- Power Consumption: 10 watts (max)
- Dimensions: 10.25"W x 1.25"H x 4.125"D
- Shipping Weight: 6 lbs.

