



[Status](#) [Live Log](#) [Config](#) [Readers](#) [Users](#) [Services](#) [Files](#) [Failban](#) [CacheEX](#) [Scripts](#) [Restart](#)

Edit Reader to_server

Reader general settings

Description:	reader to woonkamer		
Enable:	☒		
Device:	192.168..178.42,31110		
Group:		Valid values 1-64	
Fallback:	☐		
Fallback per caid:			
LB Force Fallback:	☐ Without considering reader's statistics		
Loadbalance weight:	100		
Caid:			
Ident:			
CHID:			
Class:			
Local cards:			
AU disabled:	☐		
AU Provid:			
Ratelimit ECM:		ECM Unique:	☐
Ratelimittime:		ms	
Additional ms to hold SRVID in slot:			
Cool down:	delay: ms , duration: ms. If used, you need to define both values		
ECM not found limit:			
ECM whitelist:			
ECM HeaderWhitelist:			
Drop CWs with wrong checksum:	☐		
Skip CWs checksum test:	☐		
Skip CWs checksum test only for:			
Emmcache:			
Saveemm:	☐ unknown ☐ unique ☐ shared ☐ global		
Blockemm:	☐ unknown ☐ unique ☐ shared ☐ global		

Block EMM by Len:

Reader specific settings for protocol cs357x

User:

Password:

Reader specific settings for Cccam

CCC Hop:

Reshare:

If this parameter = -1 The value off Global CCCam Reshare 10 is used.

CacheEX

Cache-EX-Mode:

 

Cache-EX Maxhop:

Cache-EX 2 ECM filter:

Cache-EX 2 filter adv.:

☐ drop csp cache ☐ allow request ☒ allow filter

Block fake cws:

☐ block fake cws

Save

OSCam Webinterface developed by Streamboard Team

Current Time: 17.01.20 | 16:16:54 **Start Time:** 12.01.20 | 14:37:59 **OSCam Run Time:** 05d 01:38:55

Process ID: 2122 **Access from:** 192.168.178.26 **Run as:** root **dm500hd Up Time:** 05d 23:58:30

OSCam: 1.20-unstable_svn **Build:** r11400 **Compiler:** mipsel-oe-linux

WebIf Style by Streamboard Team

[▲TOP](#)