



Edit Reader to-server

Reader general settings

Description:	to_server		
Enable:	☒		
Device:	192.168.178.23,321110		
Group:		Valid values 1-64	
Fallback:	☐		
Fallback per caid:			
LB Force Fallback:	☐ Without considering reader's statistics		
Loadbalance weight:	100		
Caid:			
Ident:			
CHID:			
Class:			
Local cards:			
AU disabled:	☐		
AU Provid:			
Ratelimit ECM:		ECM Unique:	☐
Ratelimittime:		ms	
Additional ms to hold SRVID in slot:			
Cool down:	delay: ms , duration: ms. If used, you need to define both values		
ECM not found limit:			
ECM whitelist:			
ECM HeaderWhitelist:			
Drop CWs with wrong checksum:	☐		
Skip CWs checksum test:	☐		
Skip CWs checksum test only for:			
Emmcache:			
Saveemm:	☐ unknown ☐ unique ☐ shared ☐ global		
Blockemm:	☐ unknown ☐ unique ☐ shared ☐ global		
Block EMM by Len:			

Reader specific settings for protocol cs378x

User:	Client1
Password:	slaapkamer

Inactivity timeout: s default 0

Reconnect timeout: s

Keepalive: ☐

Reader specific settings for Cccam

CCC Hop:

Reshare: If this parameter = -1 The value off Global CCCam Reshare 10 is used.

CacheEX

Cache-EX-Mode: ▾

Cache-EX Maxhop:

Cache-EX 2 ECM filter:

Cache-EX 2 filter adv.: ☐ drop csp cache ☐ allow request ☒ allow filter

Block fake cws: ☐ block fake cws

OSCam Webinterface developed by Streamboard Team

Current Time: 17.01.20 | 18:43:59 **Start Time:** 17.01.20 | 18:40:38 **OSCam Run Time:** 00:03:21

Process ID: 3402 **Access from:** 192.168.178.22 **Run as:** root **dm500hd Up Time:** 06d 02:25:38

OSCam: 1.20-unstable_svn **Build:** r11400 **Compiler:** mipsel-oe-linux

WebIf Style by Streamboard Team

▲TOP