

```
AAF-ufs910:~# /var/emu/oscam -c /var/keys &
AAF-ufs910:~# Warning: keyword 'pidfile' in global section not recognized
2010/12/25 11:23:21 29573AC0 s >> OSCam << cardserver started version 1.00-
unstable_svn, build #4194 (sh4-linux)
2010/12/25 11:23:21 29573AC0 s version=1.00-unstable_svn, build #4194,
system=sh4-linux-, nice=-1
2010/12/25 11:23:21 29573AC0 s client max. idle=2500 sec, debug level=0
2010/12/25 11:23:21 29573AC0 s max. logsize=unlimited
2010/12/25 11:23:21 29573AC0 s client timeout=5000 ms, fallback timeout=2500 ms,
cache delay=120 ms
2010/12/25 11:23:21 29573AC0 s auth size=4776
2010/12/25 11:23:21 29573AC0 s services reloaded: 0 services freed, 3 services
loaded
Warning: keyword 'provid' in reader section not recognized
Warning: keyword 'provid' in reader section not recognized
2010/12/25 11:23:21 29573AC0 s userdb reloaded: 0 accounts freed, 3 accounts
loaded, 0 expired, 0 disabled
2010/12/25 11:23:21 29573AC0 s signal handling initialized (type=sysv)
2010/12/25 11:23:21 29573AC0 s 809 service-id's loaded
2010/12/25 11:23:21 29573AC0 s can't open file "/var/keys/oscam.tiers" (err=2),
no tier-id's loaded
2010/12/25 11:23:21 29573AC0 s 425 provid's loaded
2010/12/25 11:23:21 29573AC0 s can't open file "/var/keys/oscam.ird" (errno=2)
irdeto guessing not loaded
2010/12/25 11:23:21 29573AC0 s monitor: disabled
2010/12/25 11:23:21 29573AC0 s camd35: disabled
2010/12/25 11:23:21 29573AC0 s newcamd: disabled
2010/12/25 11:23:21 29573AC0 s cccam: disabled
2010/12/25 11:23:21 29573AC0 s http thread started
2010/12/25 11:23:21 29573AC0 s creating thread for device /dev/ttyUSB0
2010/12/25 11:23:21 29573AC0 s creating thread for device /dev/ttyUSB1
2010/12/25 11:23:21 29573AC0 s waiting for local card init
2010/12/25 11:23:21 2A0214E8 h HTTP Server listening on port 8888
2010/12/25 11:23:21 2A8214E8 r reader thread started (thread=2A8214E8,
label=readerextern, device=/dev/ttyUSB0, detect=cd, mhz=357, cardmhz=357)
2010/12/25 11:23:21 2B0214E8 r reader thread started (thread=2B0214E8,
label=readerextern2, device=/dev/ttyUSB1, detect=cd, mhz=357, cardmhz=357)
2010/12/25 11:23:23 2A8214E8 r readerextern card detected
2010/12/25 11:23:23 2A8214E8 r using ATR from reader config
2010/12/25 11:23:23 2A8214E8 r ATR: 3B F7 11 00 01 40 96 70 70 0A 0E 6C B6 D6
2010/12/25 11:23:24 2A8214E8 r Maximum frequency for this card is formally 5
Mhz, clocking it to 3.57 Mhz
2010/12/25 11:23:24 2B0214E8 r readerextern2 card detected
2010/12/25 11:23:25 2A8214E8 r type: SECA, caid: 0100, serial: xxxxxxx, card:
Canal+ NL v10.0
2010/12/25 11:23:25 2A8214E8 r [seca-reader] provider: 1, valid: 1, name:
MANAGMENT, expiry date: 2011/02/04
2010/12/25 11:23:25 2A8214E8 r [seca-reader] SA: 11048CF0
2010/12/25 11:23:25 2A8214E8 r [seca-reader] provider: 2, valid: 1, name:
CANALDIGITAAL, expiry date: 2011/02/04
2010/12/25 11:23:25 2A8214E8 r [seca-reader] SA: 00274B18
2010/12/25 11:23:25 2A8214E8 r providers: 2 (0000,006A)
2010/12/25 11:23:25 2A8214E8 r [seca-reader] parental locked
2010/12/25 11:23:25 2A8214E8 r [seca-reader] ready for requests
2010/12/25 11:23:25 2A8214E8 r found cardsystem
2010/12/25 11:23:26 2A8214E8 r [seca-reader] no PBM for provider 1
2010/12/25 11:23:26 2A8214E8 r [seca-reader] PBM for provider 2:
C60000000000000000
2010/12/25 11:23:29 2B0214E8 r ATR: 3B F7 11 00 01 40 96 70 70 0A 0E 6C B6 D6
2010/12/25 11:23:30 2B0214E8 r Maximum frequency for this card is formally 5
Mhz, clocking it to 3.57 Mhz
2010/12/25 11:23:31 2B0214E8 r type: SECA, caid: 0100, serial: xxxxxxx, card:
```

Canal+ NL v10.0

```
2010/12/25 11:23:31 2B0214E8 r [seca-reader] provider: 1, valid: 1, name:
MANAGMENT, expiry date: 2011/02/04
2010/12/25 11:23:31 2B0214E8 r [seca-reader] SA: 11108FB7
2010/12/25 11:23:32 2B0214E8 r [seca-reader] provider: 2, valid: 1, name: TV
VLAANDEREN, expiry date: 2011/02/04
2010/12/25 11:23:32 2B0214E8 r [seca-reader] SA: 0029890F
2010/12/25 11:23:32 2B0214E8 r providers: 2 (0000,006C)
2010/12/25 11:23:32 2B0214E8 r [seca-reader] parental locked
2010/12/25 11:23:32 2B0214E8 r [seca-reader] ready for requests
2010/12/25 11:23:32 2B0214E8 r found cardsystem
2010/12/25 11:23:32 2B0214E8 r [seca-reader] no PBM for provider 1
2010/12/25 11:23:32 2B0214E8 r [seca-reader] PBM for provider 2:
8400000000000000
2010/12/25 11:23:32 29573AC0 s init for all local cards done
2010/12/25 11:23:32 2B8214E8 c plain dvbapi-client granted (anonymous, au(auto)
=0)
2010/12/25 11:23:32 2B8214E8 c dvbapi: can't open priority file
/var/keys/oscam.dvbapi
2010/12/25 11:23:36 2B8214E8 c dvbapi: [ADD PID 0] CAID: 0100 ECM_PID: 070E
PROVID: 00006A
2010/12/25 11:23:36 2B8214E8 c dvbapi: [ADD PID 1] CAID: 0100 ECM_PID: 0722
PROVID: 00006C
2010/12/25 11:23:36 2B8214E8 c dvbapi: [ADD PID 2] CAID: 0100 ECM_PID: 0646
PROVID: 00006A
2010/12/25 11:23:36 2B8214E8 c dvbapi: [ADD PID 3] CAID: 0500 ECM_PID: 0592
PROVID: 042500
2010/12/25 11:23:36 2B8214E8 c dvbapi: new program number: 1B7B (NED 1 HD)
2010/12/25 11:23:37 2B8214E8 c dvbapi: Start descrambling PID #0 (CAID: 0100) 2
2010/12/25 11:23:37 2B8214E8 c anonymous (0100&00006A/1B7B/64:49EC): found (375
ms) by readerextern (of 2 avail 2) - NED 1 HD
2010/12/25 11:23:40 2B8214E8 c dvbapi: read error 110 on fd 21
```